

PROCESS

- ▶ MIG SINGLE / DUAL PULSE
- ▶ MIG SYNERGIC / MANUAL
- ▶ MIG GAS / GASLESS
- ▶ DC TIF (LIFT ARC)
- ▶ STICK (MMA)

Duty Cycle

60% @ 300A

Generator

18 Kva

Plate Thickness

Max. 16mm

Material

- Mild Steel
- Stainless
- Carbon Steel
- Copper Steel
- Aluminium (MIG only)

FEATURES

- 300A Output
- 5" Colour LCD Screen
- 2T/4T/S4T/Spot Weld
- Suits D200 & D300 Spools
- 4 Roll Wire Drive System
- Weld Parameter Storage
- Separate Wire Feeder



UPGRADE DIGITAL REMOTE CONTROL MIG TORCH



UPGRADE PUSH PULL TORCH



SPECIFICATION

Primary Input Power	3 Phase 415V 50-60 HZ +/-15%		
Duty Cycle @ 40°C 10min	60% @ 300A 100% @ 235A		
	MIG	TIG	MMA
Effective Current (A)	15.9	12.6	17.1
Rated Input Current (A)	20.6	16.3	22.1
Rated Input Power (KW)	14.3	11.3	15.4
Welding Current Range (A)	20 – 300	10 – 300	10 – 300
Welding Voltage Range (V)	15 – 29	10.4 – 22	20.4 – 32
I Max (A)	20.5	16.5	22.0
I eff (A)	15.9	12.8	17.0
Wire Diameter Range	0.8 – 1.6mm		
Electrode Diameter Range	1.6 – 5mm		
Protection / Insulation Class	IP21S / S		
Power Factor / Efficiency	0.66 / 85.8%		
Thermal Overload	Yes		
Dimensions / Weight	H93 x L94 x W46 cm		
Weight	53 kg		
Warranty	5 Year		
Part Number	658301		

STANDARD PACKAGE INCLUSIONS

- BT Weld PULSEMIG 300 Compact Inverter Welder 415V
- BT Weld Tool Storage
- Original Binzel 36 MIG Torch 4Mt
- Twist Lock Electrode Holder 4Mt
- Earth Clamp 300Amp 4Mt
- Argon Twin Gauge Regulator
- Quick Connect Gas Hose 2Mt
- Drive Roller 0.9/1.2mm V Groove (Fitted)
- Drive Roller 1.0/1.2mm U Groove Spare 2pcs



UPGRADE OPTIONS & ACCESSORIES

AS Approved 10A 3 Phase plug	600608
AS Approved 20A 3 Phase plug (recommended)	600609
BZ24 Digital Display Remote Control MIG Torch 3Mt	92.ST.24.3
BZ24 Digital Display Remote Control MIG Torch 4Mt	92.ST.24.4
BZ36 Digital Display Remote Control MIG Torch 3Mt	92.ST.36.3
BZ36 Digital Display Remote Control MIG Torch 4Mt	92.ST.36.4
SPX24 MIG Spool Gun 9 pin 4Mt	97.SPX24.4.9
SPX24 MIG Spool Gun 9 pin 8Mt	97.SPX24.8.9
BT Weld Push Pull Torch 8Mt	92.PPX.36.8